

DESCRIPTION & USE

LEXCAN HI-PRO PVC T-JOINT COVER is a non-reinforced PVC membrane, with Elvaloy® KEE, formed into a 114 mm (4.5") diameter circle. T-JOINT COVER is used to reinforce "T" intersections in field seams and at various angle seam transitions.

FEATURES & BENEFITS

Prefabricated Membrane Accessory - provides labour savings and a more professional and consistent appearance than field cut T-Joint covers.

TECHNICAL DATA

| Typical Properties & Characteristics | |
|--------------------------------------|---------------------------------------|
| Material: | Non-reinforced PVC with Elvaloy®* KEE |
| Size: | 114 mm (4.5") diameter |
| Available Colours: | White and Grey |

* Elvaloy® KEE is a registered trademark of Dow.

PACKAGING

| | |
|-------------------|------------------|
| Quantity per Box: | 100 per box |
| Box Weight: | 2.9 kg (6.4 lbs) |

STORAGE

Store indoors, out of direct sunlight, and keep clean and dry prior to application.

INSTALLATION

Note: Prior to installation, ensure the welding surface is clean by using LEXCAN SINGLE PLY MEMBRANE CLEANER.

1. Center the T-JOINT COVER over the splice intersection. Begin welding at the center point and work towards the outside. Use the edge of the roller to crease the T-JOINT COVER into the underlying seams, to achieve a proper seal.
2. Once the T-JOINT COVER has completely cooled, using a seam probe, check all splices for voids and cold welds. Make any needed repairs.

