

LEXCOR

LEXGRIP™

## 2.4" Barbed Galvanized Steel Seam Plates

## DESCRIPTION &amp; USE

- 2.4" Barbed Galvanized Steel Seam Plates are specifically designed to assist in the mechanical attachment of roof membranes. They are for use with Lexgrip™ #14 Drill Point Heavy Duty Fasteners, #14 Drill Point Heavy Duty Stainless Steel Fasteners, and #15 Drill Point Extra Heavy Duty Membrane Fasteners.

## TECHNICAL DATA

## 2.4" BARBED GALVANIZED STEEL SEAM PLATES - PHYSICAL PROPERTIES

Part No.	Pieces / pail	Weight / pail
XHDPLATE	1000	52 lbs

Thickness: 0.040"

Diameter: 2.4"

Hole Diameter: 0.265"

Coating: AZ-55 Galvalume

## INSTALLATION

Lexgrip membrane fasteners must penetrate steel decks a minimum of 19 mm (3/4"). Using a screw gun, drive the fastener until a slight depression is seen around the plate, or with very rigid boards, watch for the plate to dimple. Note: Care must be taken not to overdrive the fastener and fracture the skin of the insulation. The fastener must be tight enough so that the plate does not turn. Factory Mutual requires that the fastener penetrate the steel deck at the top flute.



lexcor.net

Visit our video channels: <https://vimeo.com/channels/lexcoren>

## COMMERCIAL BUILDING PRODUCTS

Ontario & Western Canada  
1.800.268.2889Quebec & Eastern Canada  
1.800.363.2307