

LEXGRIP™

#15 PRE-ASSEMBLED HEAVY DUTY SCREW
WITH 2" BARBED PLATE

DESCRIPTION & USE

Lexgrip's Pre-Assembled #15 Heavy Duty Screws with 2" Barbed Galvanized Steel Seam Plates are fast to install and used to fasten membrane sheet at the laps.

TECHNICAL DATA

| #15 PA HD SCREW with 2" BARBED PLATE | | |
|--------------------------------------|-------------------|-------------------|
| Screw Length | Piece per Cartons | Weight per Carton |
| 2" | 250 | 12.25 lbs |
| 3" | 250 | 14.50 lbs |
| 4" | 250 | 16.75 lbs |
| 5" | 250 | 19.50 lbs |
| 6" | 250 | 21.25 lbs |
| 7" | 250 | 24.25 lbs |
| 8" | 250 | 26.25 lbs |
| 10" | 200 | 24.60 lbs |
| 12" | 200 | 28.20 lbs |



INSTALLATION

Allow a minimum of 19 mm (3/4") penetration through the underside of steel decks and a minimum of 19 mm (3/4") embedment in wood plank.

Using a screw gun, drive the screw until a slight depression is seen around the plate. The fastener must be tight enough so that the plate does not turn.

For best results, use a variable speed 0 - 2500 rpm screw gun. Special stand-up installation tools are available to help speed up production and relieve physical stress.

SPECIFICATION

Lap Seam Fastening (Generic) – Heavy Duty screws shall be Factory Mutual approved #15 self-tapping screws with a #3 Phillips Truss Head [pre-assembled; complete with] 50 mm (2") Barbed Galvanized Steel Seam Plates. Screws shall be coated with a corrosion resistant coating that passes 30 cycles of the Kesternich test.

Accepted Product: Lexgrip™ #15 Pre-Assembled Insulation Screw with 2" Barbed Plate by Lexcor (www.lexcor.net, Tel: 1.800.268.2889). Install in accordance with manufacturer's directions.

lexcor.net

COMMERCIAL BUILDING PRODUCTS

Ontario & Western Canada
1.800.268.2889



Quebec & Atlantic Canada
1.800.363.2307