

DESCRIPTION AND USE

LEXCAN HI-FLEX EPDM T-JOINT COVER consists of uncured EPDM membrane that has been laminated to a 25 mil EPDM based pressure sensitive tape and formed into a 140 mm (5.5") diameter circle. It is used to reinforce "T" intersections in field seams and at various angle seam transitions.

FEATURES AND BENEFITS

Exceptional Strength - will not shrink, bridge, or delaminate due to stress or movement in the roofing system.

Peel'n Stick Application - features a pressure sensitive adhesive compound for truly superior adhesive strength. The special laminate eliminates the need to apply a separate coat of adhesive to the flashing membrane.

Extremely Flexible and Mouldable - easily conforms to the most irregular of shapes and surfaces.

Durable - resists UV light, high-heat and moisture.

TECHNICAL DATA

Colour: Black

PACKAGING

100 units per box

STORAGE

Store material in original unopened packaging at temperatures between 4°C - 43°C (40°F-110°F).

SHELF LIFE

9 months when stored as recommended.

INSTALLATION INSTRUCTIONS

Surface Preparation

All work surfaces should be clean, dry, and free of dirt, dust, debris, oils, un-adhered coatings, deteriorated membrane and other contaminants that may result in a surface that is not sound or is uneven. If necessary, clean the surface to receive the HI-FLEX EPDM T-JOINT COVER with LEXCAN SINGLE PLY MEMBRANE CLEANER.

1. Apply LEXCAN HI-FLEX EPDM PA-100 PLUS Primer to the substrate or membrane where the HI-FLEX EPDM T-JOINT COVER is to be bonded. Apply primer to clean, dry surfaces in strict accordance with the instructions on the primer container. Allow primer to dry until it does not string when touched with a dry finger.
2. Carefully position the HI-FLEX EPDM T-JOINT COVER over the primed area and remove the release liner.



3. Press HI-FLEX EPDM T-JOINT COVER into position, avoiding air entrapment and wrinkles. Roll HI-FLEX EPDM T-JOINT COVER with a steel roller, ensuring complete contact.
4. Caulk all exposed HI-FLEX EPDM T-JOINT COVER edges with LEXCAN LAP SEALANT.

CAUTIONS & LIMITATIONS

- Prior to working with this or any adhesive product consult product label and Safety Data Sheet (SDS) for necessary health and safety precautions.
- Not for use on PVC roof membranes.
- Not for use in high traffic areas.