

DESCRIPTION AND USE

HI-FLEX EPDM PS POURABLE SEALER POCKET is a prefabricated pocket ideal for sealing irregular, hard-to-flash penetrations. Each pocket consists of a pre-applied pressure sensitive tape on the bottom of the base flange for uniform adherence to the membrane, as well as fast installation.

FEATURES AND BENEFITS

Prefabricated accessory - Provides labour savings, as well as a more professional and consistent appearance than field fabricating a sealant pocket.

TECHNICAL DATA

HI-FLEX EPDM PS POURABLE SEALER POCKET meets or exceeds the requirements of ASTM D 4811.

Physical Properties	
Colour:	Black
Tensile Strength:	690 kPa (100 psi)
Peel Strength @ 21°C [70°F]:	1.43 - 1.79 kg/cm (8 - 10 pli)
Shear Strength @ 21°C [70°F]:	241 - 310 kPa (35 - 45 psi)

PACKAGING

Size:	152 mm (6") diameter
Total Nominal Thickness:	2.28 mm (0.090")
Membrane:	1.52 mm (0.060")
Tape:	0.76 mm (0.030")
Units per Box:	12
Weight per Box:	4.2 kg (9.2 lbs)

STORAGE

Store indoors, out of direct sunlight, and keep clean and dry prior to installation.

SHELF LIFE

18 months from manufacture date.

INSTALLATION

Note: Prior to installation, ensure the surface for application is clean and dry. If required, use LEXCAN SINGLE PLY MEMBRANE CLEANER.



1. Apply HI-FLEX EPDM PA-100 PLUS primer with a clean scrub pad (or equivalent). Scrub the area of the membrane where the HI-FLEX EPDM PS POURABLE SEALER POCKET is to be applied, in a circular motion to achieve a thin, even layer on the membrane. The area that has been properly cleaned and primed will have a consistent color, without any streaks, and will be free from lumps or pools of primer.
2. Let the HI-FLEX EPDM PA-100 PLUS primer dry until it no longer sticks to a dry finger. As soon as the primer is dry, apply the HI-FLEX EPDM PS POURABLE SEALER POCKET. This will help reduce the risk of dust contamination and improve adhesion, especially in colder climates.
3. Apply HI-FLEX EPDM PA-100 PLUS primer to the inner wall of the HI-FLEX EPDM PS POURABLE SEALER POCKET, as well as to the surface of the material penetrating the membrane (ex. pipe). Using the stainless steel hose clamp, place at the top of the boot and tighten to projection.
4. Fill the pocket with a compatible Pourable Sealer and crown the surface to prevent ponded water.

CAUTIONS & LIMITATIONS

- Do not use HI-FLEX EPDM PS POURABLE SEALER POCKET on any pipe penetrations that exceed 71°C (160°F).
- Do not install in direct contact with asphalt or coal tar pitch.