



MULTIGRIP

FIRE RETARDANT PRIMER FOR MEMBRANES AND ADHESIVE FOR EXPANDED POLYSTYRENE INSULATION

DESCRIPTION & USE

Multigrip is a quick-setting synthetic elastomeric based liquid that forms a fireproof film when it dries.

This product is used:

- to glue expanded polystyrene panels together.
- to glue gypsum board, vapour barriers or insulation to wood or steel deck.
- as a primer for self adhesive membranes.

FEATURES & BENEFITS

- A liquid consistency which allows application with a sprayer.
- Quick drying

TECHNICAL DATA

LEXCOR MULTIGRIP	
Format	18.93 L (5 gal)
Approximate weight	32 lbs
Colour	Red
Solids content	± 40%
Coverage as an adhesive	
Solids surface	± 8 m ² /L (200 ft ² /gal)
Corrugated steel support	± 9 m ² /L (300 ft ² /gal)
Drying time with 50% H.R.	20°C (68°F)
Initial set	30 minutes
Completely set	2 hours
Application temperature	-10°C to 35°C (14°F to 95°F)
Operating temperature	-40°C to 70°C (-54°F to 158°F)
System's susceptibility to fire	
Damps	Very flammable
Dry	Fireproof
Storage life-time	12 months
VOC	459 g/L < Water and free of solvent



APPLICATION

1. The surface must be firm and free of particles, cracks, grease, oil and other substances. Must be free of frost, snow and ice.
2. Mix adequately.
3. Apply a bead in order to obtain maximum adhesion between two panels or expanded polystyrene insulation.

RESTRICTIONS

- Do not store in direct sunlight.
- Keep all unused containers closed.
- Contains extremely flammable solvents.
- Do not smoke or do any welding on the worksite.
- Avoid heat and open flames.
- Use in well ventilated areas.
- Avoid all contact with skin and avoid inhaling fumes for any lengthy period of time.
- Harmful if ingested.

lexcor.net

COMMERCIAL BUILDING PRODUCTS

Ontario & Western Canada
1.800.268.2889



Quebec & Atlantic Canada
1.800.363.2307