



FiberTite KEE TuffTrac

Product Data

FiberTite walkway and protection materials are designed to improve slip resistance, promote positive traction and offer protection from potential damage caused by dropped tools or mishandled equipment.

DESCRIPTION

FiberTite KEE TuffTrac is a high strength, textile-reinforced walkway material featuring the proprietary Seaman Corporation ELVALOY™ Ketone Ethylene Ester (KEE) formulation and embossed with a low profile diamond plate design in high visibility yellow or gray colors.



Product Detail

PHYSICAL PROPERTIES

Property	Test Method	Value/Unit
Weight	ASTM D751	50 ± 2 oz/yd ²
Thickness	ASTM D752	60 mil (nominal)
Roll Size	n/a	30 in x 100 feet
Colors	n/a	Yellow, Gray
Dimensional Stability (%)	ASTM D1204	0.5% (max)
Puncture Resistance	ASTM D751	125 lb
Grab Tensile	ASTM D752	450 lb/450 lb

APPLICATION

Walkway and protection materials are used to provide defined paths to facilitate common rooftop traffic and traffic involved in regular servicing, maintenance, and repairs. FiberTite TuffTrac is designed to improve slip resistance, promote positive traction, and offer protection from potential damage caused by dropped tools or mishandled equipment.

TuffTrac walkways are to be maintained in specific areas around roof access points (ladders, hatches, doorways, etc.), around mechanical equipment requiring periodic maintenance and as a walkway system on roof areas subject to frequent foot traffic.

Rolls of TuffTrac walkway can easily be cut to various shapes or sizes to facilitate most applications. The material is also designed to be continuously hot-air welded directly to the FiberTite roofing membrane.

For additional recommendations and requirements, please consult the most current versions of FiberTite Guide Specifications for the Installation of FiberTite Roofing Systems.



For more information on FiberTite Systems and accessories please call:
 Seaman Corporation (800) 927-8578
 International (330) 262-1111
FiberTite.com

These specifications are current as of the date of printing. Revisions or additions may be issued periodically. For a listing, presentation, and download of the most recent data, visit:

www.FiberTite.com/document-library/product-data-sheets

FiberTite® is a registered trademark of Seaman Corporation.
 ELVALOY™ is a trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow.