



## FiberClad Coated Metal

### Product Data

FiberClad is a heat weldable, polymeric coated sheet metal flashing for use with all FiberTite Roofing Systems.

#### DESCRIPTION

The polymeric coating helps extend the monolithic nature of the membrane roofing system to the metal flashing profiles. In addition to providing a hot-air weldable surface to the metal flashing, the polymeric coating protects the steel or aluminum sheet metal from environmental elements and accents the aesthetics of the finished roof system.

FiberClad is sold only as flat sheet to allow the roofing contractor to customize individual metal profiles and is included in Seaman Corporation's Commercial Warranty for FiberTite Roofing Systems.

#### APPLICATION

FiberClad metal flashing is cut and formed to meet desired flashing profiles on standard (10-ft) sheet metal equipment. FiberClad metal flashing profiles are fastened in accordance with project requirements and current FiberTite Guide Specifications and Details. Metal flashing profiles are sealed using nominal 6-in wide strips of FiberTite membrane hot air welded to the metal profile and the membrane roof system and/or flashing.

#### PHYSICAL PROPERTIES

##### 24 ga. Hot dipped G-90 Steel

Film Thickness	.020 in (0.5 mm)
Sheet Dimensions	48-in x 120-in (1.2 m x 3.0 m)

##### \*0.040 in thick 3003H14 Aluminum

Film Thickness	.020 in (0.5 mm)
Sheet Dimensions	47.5-in x 120-in (1.2 m x 3.0 m)

##### 24 ga. 304 2B Stainless Steel

Film Thickness	.020 in (0.5 mm)
Sheet Dimensions	48-in x 120-in (1.2 m x 3.0 m)

Available colors: DC196-off white, bronze, gray & white.

\*Aluminum and Stainless Steel FiberClad available in DC196 off white only.

These specifications are current as of the date of issuance. Revisions or additions may be issued periodically. For a listing, presentation, and download of the most recent data for other FiberTite products, visit:

[www.fibertite.com/document-library/product-data-sheets](http://www.fibertite.com/document-library/product-data-sheets)



**INTELLIGENT  
ROOFING SOLUTIONS**

For more information on FiberTite Systems and accessories please call:  
Seaman Corporation (800) 927-8578  
International (330) 262-1111  
[www.fibertite.com](http://www.fibertite.com)

FiberTite® is a registered trademark of Seaman Corporation.

