



FiberTite Membrane Cover-Strips

Product Data

Seaman Corporation provides FiberTite Membrane Stripping for completion of Roof Edge Metal & Field Membrane installation details.

DESCRIPTION

FiberTite Stripping is constructed from FiberTite Membrane in widths of 6" & 8" x 100' long, in thicknesses of 36-mil, 45-mil-SM, and 50-mil-XT.

Available Colors:

- Off-white (Standard)
- White
- Thermal Tan
- Energy Gray

APPLICATION

FiberTite Membrane Stripping is used:

- To seal the FiberTite Roof Membrane at the Roof Edge Metal by hot-air welding the FiberTite Stripping to roof-side flange of FiberClad Edge Metal, and hot-air welding the opposite edge of the FiberTite Stripping to the FiberTite Roof Membrane (see FiberTite Roof Edge Detail Drawings).
- As a Coverstrip for exposed fastening plates and fasteners installed through the FiberTite Roof Membrane (see FiberTite Sheet Layout Detail Drawings).



INTELLIGENT
ROOFING SOLUTIONS

For more information on FiberTite Systems and accessories please call:
Seaman Corporation (800) 927-8578
International (330) 262-1111
www.fibertite.com

FiberTite® is a registered trademark of Seaman Corporation.

These specifications are current as of the date of printing. Revisions or additions may be issued periodically. For a listing, presentation, and download of the most recent data, visit:

www.FiberTite.com/document-library/product-data-sheets

